


WAAS CH 49219 W16A	APP CRS 160°	Rwy Idg 5000 TDZE 573 Apt Elev 586
--	------------------------	---

RNAV (GPS) RWY 16
SHELBY COUNTY (EET)

⚠ DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Birmingham altimeter setting and increase all DA 63 feet and all MDA 80 feet; increase LPV all Cats, LNAV/VNAV all Cats and LNAV Cats C/D and Circling Cat C visibilities ¼ SM. Baro-VNAV NA when using Birmingham altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F).

MISSED APPROACH: Climb to 3000 direct CABVU and hold.

ASOS 134.325	BIRMINGHAM APP CON 123.8 256.8	GCO 121.725	UNICOM 122.7 (CTAF) 0
------------------------	--	-----------------------	--



4 NM Holding Pattern JUKVO 3000 ← 340° 160° → GP 3.00° TCH 52 VGSI and RNAV glidepath not coincident (VGSI Angle 3.50/TCH 57). YIBUR 2300 2300 6 NM 2.9 NM 2.3 NM * 1360 WEDAS 2.3 NM to RW16 * LNAV only RW16 3000 CABVU ↑ ✦					ELEV 586 160° to RW16 0.3% UP 5000 X 75 MIRL Rwy 16-34 REIL Rws 16 and 34	TDZE 573
CATEGORY	A	B	C	D		
LPV DA	931-1¼ 358 (400-1¼)					
LNAV/VNAV DA	1176-2 603 (600-2)					
LNAV MDA	1220-1 647 (700-1)	1220-1¾ 647 (700-1¾)	1220-2 647 (700-2)			
CIRCLING	1220-1 634 (700-1)	1340-2¼ 754 (800-2¼)	1580-3 994 (1000-3)			

SE-4, 20 MAR 2025 to 17 APR 2025

SE-4, 20 MAR 2025 to 17 APR 2025