WAAS CH 99306 W32A	APP CRS 316°	Rwy ldg 6021 TDZE 323 Apt Elev 327

RNAV (GPS) RWY 32
EAST GEORGIA RGNL (SBO)

Baro-VNAV and VDP NA when using Vidalia altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F).
When local altimeter setting not received, use Vidalia altimeter setting and increase all DA to 638 feet and all MDA 80 feet; increase LNAV Cats C/D visibility ⅛ SM, and Circling Cats C/D visibility ¼ SM. DME/DME RNP-0.3 NA. Rwy 32 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 800 then climbing left turn to 2500 direct WINSI and hold.

AWOS-3	ATLANTA CENTER	UNICOM
133.375	127.95 343.75	122.975 (CTAF) L



ELEV 327 TDZE 323



CATEGORY	A	B	C	D
LPV DA	573-1 250 (300-1)			
LNAV/VNAV DA	573-1 250 (300-1)			
LNAV MDA	780-1 457 (500-1)		780-1⅜ 457 (500-1⅜)	
CIRCLING	900-1 573 (600-1)	920-1 593 (600-1)	1000-2 673 (700-2)	1000-2¼ 673 (700-2¼)

HIRL Rwy 14-32 L

SE-4, 20 MAR 2025 to 17 APR 2025