

WAAS CH 70724 W23A	APP CRS 230°	Rwy Idg TDZE 464 Apt Elev 468	6011 464 468
--	------------------------	---	---

RNAV (GPS) RWY 23
JIMMY CARTER RGNL (ACJ)



RNP APCH-GPS.

NA Baro-VNAV NA and VDP NA when using Columbus altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 41°C. For inop ALS when using Columbus altimeter setting, increase LPV and LNAV/VNAV all Cats visibility to 1 ½ SM. Rwy 23 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Columbus altimeter setting and increase LPV DA to 876 feet and all visibilities ¼ SM; increase LNAV/VNAV DA to 881 feet and all visibilities ¼ SM; increase all MDAs 120 feet and LNAV visibility Cats C/D ½ SM, and Circling visibility Cat C ½ SM and Cat D ¼ SM. For inop ALS, increase LPV and LNAV/VNAV all Cats visibility to ¾ SM. Circling Rwy 10, 28 NA at night.

MALSF

MISSED APPROACH:
Climb to 2600 direct JIMOP and hold.

AWOS-3 128.375	ATLANTA APP CON★ 124.2 323.1	CLNC DEL 119.95	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------	---------------------------------



ELEV 468 TDZE 464		2600 JIMOP		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00°/TCH 59°).		4 NM Holding Pattern	
*LNAV only.		*1 NM to RW23		FEDLO 2200		HASER	
RW23		1 NM		4.3 NM		5.7 NM	
CATEGORY		A		B		C	
LPV DA		760-¾		296 (300-¾)			
LNAV/VNAV DA		765-¾		301 (300-¾)			
LNAV MDA		840-¾		376 (400-¾)		840-¾ 376 (400-¾)	
CIRCLING		940-1		472 (500-1)		1020-1½ 552 (600-1½) 1280-2¾ 812 (900-2¾)	

SE-4, 20 MAR 2025 to 17 APR 2025

SE-4, 20 MAR 2025 to 17 APR 2025