

WAAS CH 82739 W04A	APP CRS 047°	Rwy Idg TDZE Apt Elev	5506 797 800
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 4



CRAWFORDSVILLE RGNL (CFJ)

RNP APCH.


Baro-VNAV NA when using Greencastle altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use Greencastle altimeter setting: increase LPV DA to 1128 feet and all visibilities ¼ SM, LNAV/VNAV DA to 1118 feet and all visibilities ¼ SM; increase all MDA 60 feet and Circling Cats C and D visibilities ¼ SM. Rwy 4 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climb to 2700 direct CONUM and hold.

AWOS-3PT 125.65	INDIANAPOLIS APP CON 119.05 317.8	UNICOM 122.8 (CTAF)
---------------------------	---	-------------------------------



CATEGORY	A	B	C	D
LPV DA	1076-7/8		279 (300-7/8)	
LNAV/VNAV DA	1066-7/8		269 (300-7/8)	
LNAV MDA	1240-1	443 (500-1)	1240-1 3/8	443 (500-1 3/8)
CIRCLING	1240-1 440 (500-1)	1260-1 460 (500-1)	1440-1 3/4 640 (700-1 3/4)	1520-2 1/4 720 (800-2 1/4)



EC-2, 20 MAR 2025 to 17 APR 2025

EC-2, 20 MAR 2025 to 17 APR 2025