

WAAS CH 61316 W19A	APP CRS 188°	Rwy Idg TDZE 961 Apt Elev 969
--	------------------------	---

RNAV (GPS) RWY 19
LAFAYETTE MUNI (3M7)

RNP APCH - GPS

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 46°C.
▲ NA Obtain local altimeter setting on CTAF; when not received, use Bowling Green altimeter setting: increase LPV DA to 1344 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 1502 feet and all visibilities ½ SM; increase all MDAs 140 feet and visibility LNAV Cat C ¼ SM, Cat D ½ SM, and Circling Cat C and D ½ SM. Rwy 19 helicopter visibility reduction below 1 SM NA.

MISSED APPROACH:
Climb to 3000 direct
HETAP and hold.

NASHVILLE APP CON
118.4 360.7

UNICOM
122.8 (CTAF)

MSA RW19 25 NM

3100



(IAF) FUPU
2900 NoPT
188° (6.6)

4 NM

008°
188°
2500
188°
(6.1)

(FAF) GALAY

1129

OLLW
1.8 NM to
RW19

1140



1099±



1132±



1140



1132±



1140



1132±



1140



1132±



1140



1132±



1140



1132±



1140



1132±



1140



1132±



1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

1132±

1140

