

WAAS CH 63135 W32A	APP CRS 323°	Rwy Idg TDZE Apt Elev	4400 1800 1800
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 32

SMITH CENTER MUNI (K82)



RNP APCH - GPS.

⚠

Baro-VNAV and VDP NA when using CNK altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C. When local altimeter setting not received, use CNK altimeter setting: increase LPV DA to 2174 feet; increase LNAV/VNAV DA to 2224 feet and all visibilities ¼ SM; increase all MDAs 180 feet, and Circling all visibilities ½ SM.

MISSED APPROACH: Climb to 3900 direct LAYIP and hold.

AWOS-3PT 118.45	MINNEAPOLIS CENTER 119.4 278.8	UNICOM 122.8 (CTAF) 0
---------------------------	--	---------------------------------



3900

↑

LAYIP

✴

WULOS

3600

JUXUL

4 NM Holding Pattern

143° → 6000

← 323° 3700

1.4 NM to RW32

1.4 NM

4.1 NM

6.5 NM

323°

3600

GP 3.00°

TCH 40

CATEGORY

A

B

C

D

LPV DA

2000-1

200 (200-1)

NA

LNAV/VNAV DA

2050-1

250 (300-1)

NA

LNAV MDA

2300-1

500 (500-1)

NA

CIRCLING

2480-1

680 (700-1)

2580-1

780 (800-1)

NA