

ILS or LOC RWY 3

LOC I-COF 109.1	APCH CRS 027°	Rwy Idg TDZE Arpt Elev 5 8	[USAF]	PATRICK SFB (KCOF)																				
DME required																								
▼ * When ALS inop, increase RVR to 40 and vis to ¾ mile. ** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CD vis to 1½ miles. *** Circling not authorized NW of Rwy 3-21. When Rwy 29 VGSi inop, circling to Rwy 29 NA at night. When circling to Rwy 29 at night, operational VGSi required, remain on or above VGSi glidepath until threshold.			ALSF-1 A1 MISSED APPROACH: Climb to 600, then climbing right turn to 3000 and intercept COF TACAN R-110 direct ZEVEX/COF 12 DME and hold.																					
ATIS ★ 119.175 273.5	ORLANDO APP CON ★ 132.65 281.425	TOWER ★ 133.75 269.375	GND CON ★ 124.35 335.8	CLNC DEL ★ 118.4 289.4																				
ELEV 8	TDZE 5	Rwy 29 Idg 3692'																						
EMERG SAFE ALT 100 NM 3000																								
<table border="1"> <thead> <tr> <th>CATEGORY</th> <th>A</th> <th>B</th> <th>C</th> <th>D</th> </tr> </thead> <tbody> <tr> <td>S-ILS 3 *</td> <td>205/24</td> <td>200</td> <td>(200-½)</td> <td></td> </tr> <tr> <td>S-LOC 3 **</td> <td>460/24</td> <td>455 (500-½)</td> <td>460/45</td> <td>455 (500-¾)</td> </tr> <tr> <td>*** CIRCLING</td> <td>520-1</td> <td>512 (600-1)</td> <td>540-1½ 532 (600-1½)</td> <td>560-2 552 (600-2)</td> </tr> </tbody> </table>					CATEGORY	A	B	C	D	S-ILS 3 *	205/24	200	(200-½)		S-LOC 3 **	460/24	455 (500-½)	460/45	455 (500-¾)	*** CIRCLING	520-1	512 (600-1)	540-1½ 532 (600-1½)	560-2 552 (600-2)
CATEGORY	A	B	C	D																				
S-ILS 3 *	205/24	200	(200-½)																					
S-LOC 3 **	460/24	455 (500-½)	460/45	455 (500-¾)																				
*** CIRCLING	520-1	512 (600-1)	540-1½ 532 (600-1½)	560-2 552 (600-2)																				