

WAAS

CH 81825

W04A

APP CRS

043°

Rwy Idg

7500

TDZE

69

Apt Elev

70

RNAV (GPS) RWY 4L

BATON ROUGE METRO, RYAN FLD (BTR)


⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C (23°F) or above 54°C (130°F).
DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Hammond altimeter setting. When local altimeter setting not received, use Hammond altimeter setting and increase all DA 91 feet and all MDA 100 feet; increase LPV visibility ¼ mile all Cats, LNAV/VNAV visibility ½ mile all Cats and LNAV Cat C/D visibility ¼ mile, Circling Cat C/D visibility ¼ mile. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:

Climb to 2300 direct KUREC and hold.

ATIS	BATON ROUGE APP CON★	RYAN TOWER★	GND CON	CLNC DEL	UNICOM
125.2	120.3 278.3	118.45 (CTAF) 257.8	121.9	119.4	122.95



ELEV 70

TDZE 69

4 NM Holding Pattern

IBEKY

2800

223°

043°

GP 3.00°

TCH 55

2000

043°

GOCET

2000

HOGTO

2.2 NM to RW04L

*1.6 NM to RW04L

RW04L

*820

2300

KUREC

*LNAV only.

CATEGORY	A	B	C	D
LPV DA	345-7/8 276 (300-7/8)			
LNAV/VNAV DA	656-2 587 (600-2)			
LNAV MDA	620-1 551 (600-1)	620-15/8 551 (600-15/8)		
CIRCLING	620-1 550 (600-1)	660-1 590 (600-1)	780-2 710 (800-2)	840-2½ 770 (800-2½)

TDZ/CL Rwy 22R

HIRL Rwys 13-31 and 4L-22R

MIRL Rwy 4R-22L