

EC-1, 17 APR 2025 to 15 MAY 2025

NOTE: RADAR required.

NOTE: RNAV 1.

NOTE: DME/DME/IRU or GPS required.

NOTE: Expect Rwy 21L.

NOTE: Jet aircraft descend via Mach number until intercepting 280K. Maintain 280K until slowed by the STAR.

NOTE: For use when DTW landing south or west. When DTW landing north, file and expect the CUUGR RNAV STAR.

NOTE: GGUCE TRANSITION: Except for flights originating in Canada, do not file, to be assigned by ATC.

D-ATIS
133.675
DETROIT APP CON
126.225 284.0

BOBTA

1500
227°
(63)

JAIBE

1500
226°
(23)

WLFMN
FL240 280K

MAVW

10000
271°
(21)

10000
273°
(20)

GGUCE

15000
274°
(23)

VYPRE

15000
271°
(29)

DONEO

10 NM
091°
271°

1dkg KDTW

306°
(4)

RYEDR

7000 210K

306°
(4)

GOHST

7000 210K

306°
(4)

CHZTR

7000

254°
(A)

254°
(12)

TPGUN

14000 280K
11000

254°
(A)

254°
(12)

HLIWD

10000
8000

10 NM
090°

MAVW

8000
270°
(27)

10000
271°
(21)

10000
273°
(20)

GGUCE

15000
274°
(23)

VYPRE

15000
271°
(29)

DONEO

10 NM
091°
271°

ARRIVAL ROUTE DESCRIPTION

BOBTA TRANSITION (BOBTA.TPGUN2)

DONEO TRANSITION (DONEO.TPGUN2)

GGUCE TRANSITION (GGUCE.TPGUN2)

From TPGUN on track 254° to cross HLIWD between 8000 and 10000, then on track 254° to CHZTR at 7000, then on track 306° to cross GOHST at 7000 and at 210K, then on track 306° to cross RYEDR at 7000 and at 210K, then on track 306°. Expect RADAR vectors to final approach course.

LOST COMMUNICATIONS:
From RYEDR, execute ILS Rwy 21L approach.

NOTE: Chart not to scale.

EC-1, 17 APR 2025 to 15 MAY 2025