

LOC/DME I-DIK

108.3

Chan 20

APP CRS

320°

Rwy Idg

7301

TDZE

2587

Apt Elev

2592

ILS or LOC RWY 32

DICKINSON/THEODORE ROOSEVELT RGNL (DIK)

DME required.

RNP APCH - GPS. From NEXRU or YURTS.

▼

NA

Use I-DIK DME when on the localizer course. For inop ALS, increase S-LOC 32 Cat C/D visibility to 1½ SM.

MALSR

AS

5

5

5

MISSED APPROACH: Climb to 3000, then climbing right turn to 5000 direct DIK VORTAC and hold, continue climb-in-hold to 5000.

ASOS 118.375	MINNEAPOLIS CENTER 124.25 236.825	UNICOM 123.0 (CTAF) 1
-----------------	--------------------------------------	---------------------------------

The diagram illustrates the ILS/LOC RWY 32 approach. Key features include:

- Localizer:** LOC 108.3, Chan 20. A 3564' obstacle is noted.
- Initial Approach:** From 3000' to 5000', a 183° turn to 320°.
- Approach Path:** 5000' to HOLZR (10.8), then 320° to DIK (10.8).
- Final Approach:** 5000' NoPT (7.1) to YURTS, then 320° to DIK (14.9).
- Obstacles:** 3564' (A), 2616' (A), 2703' (A), 2653' (A), 4700' X 75' (A).
- MSA:** Minimum Safe Altitude 4600' for 25 NM.
- Ullin:** 5000' NoPT (27.2) to ULLIN.

3000	5000	DIK		
APPUL I-DIK 4.2	HOLZR I-DIK 8.8	Remain within 10 NM		
I-DIK 1.4	I-DIK 2.5	5000		
3540	320°	GS 3.00° TCH 50		
1.2	1.7	4.6 NM		
CATEGORY	A	B	C	D
S-ILS 32	2787-½ 200 (200-½)			
S-LOC 32	3000-½	413 (500-½)	3000-¾	413 (500-¾)
CIRCLING	3060-1	468 (500-1)	3120-1½	3200-2
			528 (600-1½)	608 (700-2)

This diagram provides a detailed view of the approach, showing the 320° heading, 5000' altitude, and various obstacles. Key data points include:

- Obstacle 2653' (A) at 1301' X 150'.
- Obstacle 4700' X 75' (A) with 0.4% UP slope.
- Obstacle 2616' (A) at 320°.
- Obstacle 3540' (A) at 320°.

DICKINSON, NORTH DAKOTA

Orig 03NOV22

DICKINSON/THEODORE ROOSEVELT RGNL (DIK)

46°48'N-102°48'W

ILS or LOC RWY 32