

SC-3, 17 APR 2025 to 15 MAY 2025

TOP ALTITUDE:
ASSIGNED BY ATC

TAKEOFF MINIMUMS

Rwy 8R: FLOGS and NOCHI Transitions standard with minimum climb of 500' per NM to 6000. GREBE and SLINK Transitions standard with minimum climb of 500' per NM to 13500.

Rwy 22: FLOGS and NOCHI Transitions standard with minimum climb of 515' per NM to 7200. GREBE and SLINK Transitions standard with minimum climb of 515' per NM to 13500.

Rwy 26L: FLOGS and NOCHI Transitions standard with minimum climb of 570' per NM to 6800. GREBE and SLINK Transitions standard with minimum climb of 570' per NM to 13500.

D-ATIS
120.0 254.3
CLINC DEL
125.0 379.1
GND CON
121.9 348.6
EL PASO TOWER
118.3 239.275
EL PASO DEP CON
119.15 263.0
ALBUQUERQUE CENTER
128.2 285.5

SLINK

FL180
*9800
004°
(23)

BOATY

FL180
*9800
318°
(60)

RUTR

FL180
*12400
304°
(85)

GREBE

FL180
*12400
304°
(85)

N

NOTE: Chart not to scale.

(NARRATIVE ON FOLLOWING PAGE)

- NOTE: Takeoff Rwy 8R, do not exceed 220K until passing JAPOD.
- NOTE: Takeoff Rwy 26L, do not exceed 220K until passing 4462.
- NOTE: For use by Turbojet aircraft only.
- NOTE: RADAR required for non-GPS equipped aircraft.
- NOTE: DME/DME/IRU or GPS required.
- NOTE: RNAV 1.

ATKNN FIVE DEPARTURE (RNAV)

EL PASO, TEXAS
EL PASO INTL (ELP)

ATKNN5.ATKNN) 21JUL16

SC-3, 17 APR 2025 to 15 MAY 2025