

LOC I-EFD 111.1	APP CRS 354°	Rwy Idg TDZE Apt Elev 9001 28 33
---------------------------	------------------------	--

ILS Z or LOC Z RWY 35L
ELLINGTON (EFD)


RADAR required for procedure entry.

⚠ Circling NA west of Rwy 17R-35L. DME from EFD TACAN. Simultaneous reception of I-EFD and EFD DME required. Inop table does not apply to S-ILS 35L. For inop ALS, increase S-LOC 35L Cat C/D/E visibility to 1½ SM. For inop ALS when using JUVUM fix minimums, increase S-LOC 35L Cat C/D/E visibility to RVR 6000.

MALSF

⚠ MISSED APPROACH: Climb to 700 then climbing right turn to 3100 on VUH VOR/DME R-320 to WATFO INT/VUH 9.3 DME and hold. (TACAN aircraft climb to 700 then climbing right turn to 3100 on EFD TACAN R-136 to WATFO/EFD 16 DME and hold southeast, left turn, 316° inbound).

ATIS 135.575 269.9	HOUSTON APP CON 134.45 284.0	ELLINGTON TOWER 126.05 253.5	GND CON 121.6 275.8
------------------------------	--	--	-------------------------------



ELEV 33 **D** **TDZE 28**

HIRL Rwy 4-22 and 17R-35L
TDZ/CL Rwy 17R, 22 and 35L

TWR 116

FAF to MAP 5.7 NM

Knots: 60 90 120 150 180
Min:Sec: 5:42 3:48 2:51 2:17 1:54

LOC only.

WATFO INT

JUVUM EFD 2.5

BAYUU EFD 1.4

MARZY INT EFD 7.1

PAHSU INT EFD 15

GS 3.00° TCH 54

CATEGORY	A	B	C	D	E
S-ILS 35L	228/40 200 (200-¾)				
S-LOC 35L	620/40	592 (600-¾)	620-1⅓	592 (600-1⅓)	
C CIRCLING	620-1	587 (600-1)	620-1¾ 587 (600-1¾)	640-2 607 (700-2)	700-2¼ 667 (700-2¼)
JUVUM FIX MINIMUMS (DME REQUIRED)					
S-LOC 35L	440/40	412 (500-¾)	440/50	412 (500-1)	
C CIRCLING	500-1	467 (500-1)	580-1½ 547 (600-1½)	640-2 607 (700-2)	700-2¼ 667 (700-2¼)

SC-5, 17 APR 2025 to 15 MAY 2025

SC-5, 17 APR 2025 to 15 MAY 2025