

WAAS CH 50316 W16A	APP CRS 159°	Rwy Idg 5387 TDZE 341 Apt Elev 341
--	------------------------	---

RNAV (GPS) RWY 16

HAWKINS FLD (HKS)

⚠

Baro-VNAV NA when using Jackson-Medgar Wiley Evers Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -6°C (22°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Jackson-Medgar Wiley Evers Intl altimeter setting and increase all DA 19 feet and all MDA 20 feet. Increase LNAV/VNAV all Cats and LNAV Cats C/D visibilities ½ mile and Circling Cat C ¼ mile. For inop MALS R when using Jackson-Medgar Wiley Evers Intl altimeter setting increase LNAV/VNAV all Cats to 1½.

MALS R

MISSED APPROACH:

Climb to 2000 direct JILHO and hold.

ASOS 120.625	JACKSON APP CON ★ 123.9 319.2	HAWKINS TOWER ★ 119.65 (CTAF) 0 257.8	GND CON 121.9 239.0	CLNC DEL 121.9 (When twr closed)	UNICOM 122.95
------------------------	---	---	-------------------------------	---	-------------------------

30 NM to OCARO (NoPT)
2400
5 NM to OCARO
2000
069°
OCARO

4 NM
339°
159°
(IF/IAF) OCARO

1900
159°
(FAF) GUGWA

UTUWI 1.5 NM to RW16
554
526
533±
627
362
RW16
833
1537
668
507
641
742
2409

30 NM to OCARO
2000
069°
OCARO
30 NM to OCARO
3500

MISSED APCH FIX
JILHO
159°
339°
4 NM

4 NM Holding Pattern
OCARO
2000
339°
159°
159°
1900
GUGWA
UTUWI 1.5 NM to RW16
RW16
GP 3.00°
TCH 56
6.9 NM
3.2 NM
1.5 NM
*860
*LNAV only.
2000
JILHO

CATEGORY	A	B	C	D
LPV DA		542-½	201 (300-½)	
LNAV/VNAV DA		677-⅝	336 (400-⅝)	
LNAV MDA	780-½	439 (500-½)	780-¾	439 (500-¾)
CIRCLING	860-1 519 (600-1)	880-1 539 (600-1)	1140-2¼ 799 (800-2¼)	1320-3 979 (1000-3)

ELEV 341
TDZE 341
159° to RW16
91
5387 X 150
TWR 397
0.3% UP
3431 X 150
34
376
REIL Rwy 34
HIRL Rwy 16-34
MIRL Rwy 11-29

JACKSON, MISSISSIPPI

Amtd 2A 11DEC14

32°20'N-90°13'W

HAWKINS FLD (HKS)

RNAV (GPS) RWY 16