


WAAS CH 90101 W17B	APP CRS 170°	Rwy Idg TDZE 499 Apt Elev 501	7800
--	------------------------	---	-------------

RNAV (GPS) Y RWY 17L
LOUISVILLE MUHAMMAD ALI INTL (SDF)

RNP APCH - GPS. Simultaneous approach authorized. Circling Rwy 11 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -13°C or above 54°C. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 6000.	MALSRL 	MISSED APPROACH: Climb to 1000 then climbing left turn to 3000 direct IIU VORTAC and hold, continue climb-in-hold to 3000.
---	------------	--

D-ATIS 118.725	LOUISVILLE APP CON 132.075 327.0	LOUISVILLE TOWER 124.2 257.8	GND CON 121.7 348.6	CLNC DEL 126.1 275.8	CPDLC
--------------------------	--	--	-------------------------------	--------------------------------	-------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.32/TCH 71).					
RACRR		MORKK		SLGRR	
4000		3000		2500	
GP 3.00°		TCH 55		1320	
3.5 NM		2.3 NM		3.7 NM	
A		B		C	
LPV DA		699/18		200 (200-½)	
LNAV/VNAV DA		909/40		410 (500-¾)	
LNAV MDA		920/24		920/40	
1040-1		1140-1		1160-1¾	
539 (600-1)		639 (700-1)		659 (700-1¾)	
CIRCLING		1400-3		899 (900-3)	

