WAAS CH 65601 W09A	APP CRS 094°	Rwy ldg 6000 TDZE 33 Apt Elev 33

RNAV (GPS) RWY 9L
MELBOURNE ORLANDO INTL (MLB)

RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 2°C or above 54°C. Rwy 9L helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 2000 direct LIQNI and hold.

ATIS	ORLANDO APP CON	MELBOURNE TOWER ★	GND CON	CLNC DEL	CLNC DEL	UNICOM
132.55	132.65 281.425	118.2 (CTAF) L 257.8	121.9	121.9	132.65 (When twr closed)	122.95



SE-3, 17 APR 2025 to 15 MAY 2025



CATEGORY	A	B	C	D
LPV DA	283-¾ 250 (300-¾)			
LNAV/VNAV DA	473-1¼ 440 (500-1¼)			
LNAV MDA	480-1 447 (500-1)		480-1⅜ 447 (500-1⅜)	
CIRCLING	500-1 467 (500-1)	560-1 527 (600-1)	680-1¾ 647 (700-1¾)	880-2¾ 847 (900-2¾)

REIL Rwy 27L L
HIRL Rwy 9R-27L L
MIRL Rwys 5-23 and 9L-27R L
TDZ/CL Rwy 9R