

WAAS CH 53422 W09A	APP CRS 093°	Rwy Idg 8002 TDZE 8 Apt Elev 8
--	------------------------	---

RNAV (GPS) RWY 9L


MIAMI-OPA LOCKA EXEC (OPF)

Baro-VNAV NA when using Miami Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 43°C (109°F). DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Miami Intl altimeter setting and increase all DA/MDA 20 feet and Circling Cat D visibility ¼ SM. For inop MALSR, increase LNAV/VNAV all Cats visibility to 1 mile, LNAV Cats A and B visibility to 1 mile and Cats C and D visibility to 1½ miles. For inop MALSR, when using Miami Intl altimeter setting, increase LPV all Cats visibility to ¾ mile, LNAV/VNAV all Cats visibility to 1½ miles and LNAV Cats A and B visibility to 1 mile. Inop table does not apply to LPV all Cats. Caution: Lights on highway 0.7 NM north may be mistaken for runway.

MALSR

MISSED APPROACH:
Climb to 2000 direct JOLYN and on track 076° to JANUS and hold.

ATIS 125.9	MIAMI APP CON 128.6 306.975	OPA LOCKA TOWER ★ 134.675 (CTAF) 0	GND CON 120.025	CLNC DEL 119.2	GCO 119.45
----------------------	---------------------------------------	--	---------------------------	--------------------------	----------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 55).

4 NM Holding Pattern

OKANE

SAZBO

ZOLTA 1.5 NM to RW09L

RW09L

*520

*LNAV only

GP 3.00° TCH 51

2000

JOLYN

tr 076°

JANUS

CATEGORY	A	B	C	D
LPV DA		258-¾	250 (300-¾)	
LNAV/VNAV DA		321-¾	313 (400-¾)	
LNAV MDA		420-¾	412 (500-¾)	
CIRCLING	540-1	532 (600-1)	620-1¾ 612 (700-1¾)	740-2¼ 732 (800-2¼)

ELEV 8

TDZE 8

MIRL Rwy 9R-27L
HIRL Rwy 9L-27R and 12-30 0