RNAV (RNP) Z RWY 26L

MIAMI INTL (MIA)

APP CRS	Rwy Idg	10220
272°	TDZE	9
	Apt Elev	9

RNP AR APCH-GPS.

Simultaneous approach authorized. For uncompensated Baro-VNAV systems, procedure NA below 8°C or above 54°C. For inop ALS, increase RNP 0.20 visibility to RVR 5500 for all Cats and increase RNP 0.30 visibility to RVR 6000 for all Cats.

MALSF

MISSED APPROACH: Climb to 800 then climbing right turn to 4000 direct BRBRA and hold, continue climb-in-hold to 4000.

D-ATIS	MIAMI APP CON	MIAMI TOWER	GND CON		CLNC DEL	CPDLC
ARR 119.15	124.85 322.3	118.3 256.9	121.8 (8L/8R/12/26L/26R)	348.6	135.35	
DEP 133.675			127.5 (9/27/30)			







CATEGORY	A	B	C	D
RNP 0.20 DA		368/40	359 (400-¾)	
RNP 0.30 DA		418/50	409 (500-1)	

AUTHORIZATION REQUIRED

SE-3, 17 APR 2025 to 15 MAY 2025
SE-3, 17 APR 2025 to 15 MAY 2025