

ST LOUIS, MISSOURI

AL-360 (FAA)



25107

WAAS CH 78121 W12B	APP CRS 123°	Rwy ldg 10552 TDZE 540 Apt Elev 617
--	------------------------	--

RNAV (GPS) Y RWY 12R
ST LOUIS LAMBERT INTL (STL)

RNP APCH - GPS. ▼ Rwy 12R helicopter visibility reduction below RVR 4000 NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Simultaneous approach authorized with Rwy 11. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For inop ALS, increase LPV Cat E visibility to RVR 4000, LNAV/VNAV all Cats visibility to 1½ SM, LNAV Cats A/B visibility to RVR 5500, and LNAV Cat C/D/E visibility to 1¾ SM.	MALSR 	MISSED APPROACH: Climb to 5000 direct FONTI and hold, continue climb-in-hold to 5000.
--	-----------	---

D-ATIS 125.025 379.925	ST. LOUIS APP CON 132.125 360.6	ST. LOUIS TOWER 118.5 257.7	GND CON 121.9 348.6 (Inbound) 121.65 377.175 (Outbound) 118.925 227.125 (Rwy 11/29)	CLNC DEL 119.5 363.1	CPDLC
--	---	---------------------------------------	---	--------------------------------	-------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00°/TCH 71).					5000 ↑	FONTI △
PAULY	NAIRN	TUDNE				
4500	3600	2400	1.3 NM to RW12R			
GP 3.00° TCH 54	2400		RW12R			
5.3 NM		4.9 NM	4.4 NM	1.3		
CATEGORY	A	B	C	D	E	
LPV DA	740/18 200 (200-½)					
LNAV/ VNAV DA	1103-1¼ 563 (500-1¼)					
LNAV MDA	1020/40 480 (500-¾)		1020/50 480 (500-1)			

ST LOUIS, MISSOURI
Amdt 1E 17APR25

38°45'N-90°22'W

ST LOUIS LAMBERT INTL (STL)
RNAV (GPS) Y RWY 12R

NC-3, 17 APR 2025 to 15 MAY 2025

NC-3, 17 APR 2025 to 15 MAY 2025