



WAAS CH 82409 W13A	APP CRS 128°	Rwy Idg TDZE 809 Apt Elev 809
--	------------------------	---

RNAV (GPS) Y RWY 13R
SAN ANTONIO INTL (SAT)

RNP APCH - GPS.			ALSF-2 	MISSED APPROACH: Climb to 3100 direct POYIG and on track 171° to EMBOW and hold.		
  Circling NA northwest of Rwy 4 and 13R. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 6000 and LNAV Cats C and D visibility to 1½ SM.						
D-ATIS 118.9	SAN ANTONIO APP CON 125.1 307.0	SAN ANTONIO TOWER 119.8 257.8	GND CON 121.9 348.6	CLNC DEL 126.7	CPDLC	



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 75).				3100	POYIG	tr 171°	EMBOW
GP 3.00° TCH 58				4000	3200	2200	2200
				2.5 NM	3.4 NM	2.3 NM	1.9 NM
CATEGORY	A	B	C	D			
LPV DA	1009/18			200 (200-½)			
LNAV/VNAV DA	1221/40			412 (500-¾)			
LNAV MDA	1480/24	671 (700-½)	1480-1½	671 (700-1½)			
CIRCLING	1480-1	671 (700-1)	1480-2	671 (700-2)	1520-2¼	711 (800-2¼)	