

RNAV (GPS) RWY 10
SAVANNAH/HILTON HEAD INTL (SAV)

T For inop ALS increase LNAV/VNAV all Cats visibility to 1 $\frac{1}{2}$ SM, increase LNAV Cat C/D to RVR 6000. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Hilton Head Island altimeter setting and increase LPV DA to 296 feet and all visibilities to RVR 2000, increase LNAV/VNAV DA to 596 feet and all visibilities to 1 $\frac{1}{2}$ SM, increase all MDAs 80 feet and LNAV Cat C/D visibility to RVR 5000. For inop ALS when using Hilton Head Island altimeter setting, LNAV/VNAV all Cats visibility to 1 $\frac{1}{2}$ SM, increase LNAV Cat C/D visibility to 1 $\frac{1}{2}$ SM. VDP and Baro-VNAV NA when using Hilton Head Island altimeter setting.



MISSED APPROACH:
Climb to 2500 direct
TELOE and hold.

30 NM to TLEE (NoPT)

TLEE

2600

186°

006°

4 NM

276°

2600 NoPT

186°

(5)

(IAF) WOXIT

2000

096°

096°

2600 NoPT

006° (5)

(IF/IAF) TLEE

(IAF) ZUTOX

R-3005C

R-3005D

1548

Λ

351

Λ

097°

(FAF) SOVIE

160

Λ

180

RW10

Λ 397

Λ 1493

Λ 192

531

Λ

424

424

276°

30 NM to WOXIT

186°

276°

WOXIT

2600

097°

277°

4 NM

TELOE

30 NM to ZUTOX

006°

276°

ZUTOX

2600

ELEV	50	D	TDZE	30
------	----	---	------	----

TDZ/CL Rwy 10
REIL Rwy 19 and 28 **L**
HIRL Rwy 1-19 and 10-28 **L**

SE-4, 17 APR 2025 to 15 MAY 2025