

WAAS
CH **73005**
W12A

APP CRS
126°

Rwy ldg
TDZE
Apt Elev **8279**
3963
3967

SCOTTSLUFF/WESTERN NEBRASKA RGNL/WM B HEILIG FLD (BTF)

RNAV (GPS) RWY 12

24249

When local altimeter setting not received, use Alliance altimeter setting and increase all DAs 91 feet and all MDAs 100 feet; increase LPV, LNAV/VNAV, LNAV Cat A/B and Circling Cat B visibilities ¼ mile; increase LNAV and Circling Cat C/D visibilities ½ mile. For inoperative MALSR, when using Alliance altimeter setting, increase LPV all Cats visibility to 1¼, and LNAV Cat A visibility to 1. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C (-7°F) or above 41°C (105°F). Baro-VNAV NA when using Alliance altimeter setting. VDP NA when using Alliance altimeter setting. DME/DME RNP-0.3 NA.

MALSR

MISSED APPROACH:
Climb to 6700 direct
HAKAB and hold.

ASOS 121.025	DENVER CENTER 127.95 338.2	UNICOM 123.0 (CTAF) 1
------------------------	--------------------------------------	---------------------------------

Procedure NA for arrivals at ALBIN V81 southwest bound and arrivals at SPONS V81-V169 northbound.

ELEV 3967

D

TDZE 3963

HIRL Rwy 12-30 1

MRL Rwy 5-23 1

7 NM Holding Pattern		LEDSE	CAPGA		RW12			
6900		←305°	125°→	125°	*2.1 NM to RW12			
GP 3.00°		5700		126°				
TCH 57		6.1 NM		3.1 NM	2.1 NM			
CATEGORY	A	B	C	D				
LPV DA	4213-½ 250 (300-½)							
LNAV/VNAV DA	4340-¾ 377 (400-¾)							
LNAV MDA	4700-½ 737 (800-½)		4700-1½ 737 (800-1½)		4700-1¾ 737 (800-1¾)			
CIRCLING	4700-1 733 (800-1)		4700-2 733 (800-2)		4740-2½ 773 (800-2½)			

SCOTTSLUFF, NEBRASKA

SCOTTSLUFF/WESTERN NEBRASKA RGNL/WM B HEILIG FLD (BTF)

Amdt 1A 30JAN20

41°52'N-103°36' W

RNAV (GPS) RWY 12