

LOC I-FSD	APP CRS	Rwy Idg	8999
109.9	030°	TDZE	1424
		Apt Elev	1430

ILS or LOC RWY 3

JOE FOSS FLD (FSD)

T

A

ASR

-31°C

MALSR

MISSED APPROACH: Climb to 3400 then left turn direct FSD VORTAC and hold.

ATIS	SIoux FALLS APP CON *	SIoux FALLS TOWER *	GND CON	UNICOM
126.6	125.8 284.725	118.3 (CTAF) 0 257.8	121.9 348.6	122.95

ADF or RADAR REQUIRED

ALTERNATE MISSED APCH FIX

MSA FS 25 NM

One Minute Holding Pattern		FS LOM RADAR	3400	FSD
3400 ← 210° 030° → 3400		3336	MAREY INT	* LOC only
GS 300° TCH 54			*1940	
		4.3 NM	1.4 NM	
CATEGORY	A	B	C	D
S-ILS 3	1674/24 250 (300-½)			
S-LOC 3	1940/24	516 (600-½)	1940/55	516 (600-1)
CIRCLING	1960-1 530 (600-1)	1980-1 550 (600-1)	2060-1¾ 630 (700-1¾)	2200-2½ 770 (800-2½)
MAREY FIX MINIMUMS (DUAL VOR RECEIVERS REQUIRED)				
S-LOC 3	1800/24	376 (400-½)	1800/35	376 (400-¾)
CIRCLING	1960-1 530 (600-1)	1980-1 550 (600-1)	2060-1¾ 630 (700-1¾)	2200-2½ 770 (800-2½)
ELEV 1430 D TDZE 1424				
REIL Rwy 15 and 33 HIRL Rwy 3-21 and 15-33 MIRL Rwy 9-27 TDZ/CL Rwy 21				
FAF to MAP 5.7 NM				
Knots 60 90 120 150 180				
Min:Sec 5:42 3:48 2:51 2:17 1:54				

SIoux FALLS, SOUTH DAKOTA

Amdt 27G 18JUN20

43°35'N-96°45'W

JOE FOSS FLD (FSD)

ILS or LOC RWY 3