

WAAS CH 70524 W32A	APP CRS 321°	Rwy Idg 4927 TDZE 621 Apt Elev 623
--	------------------------	---


RNAV (GPS) RWY 32
TOLEDO EXEC (TDZ)

RNP APCH.


T Circling Rwy 14 NA at night. Baro-VNAV NA when using Toledo Express altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 54°C (130°F). Rwy 32 helicopter visibility reduction below ¼ SM NA. When local altimeter setting not received, use Toledo Express altimeter setting and increase LPV DA to 914, LNAV/VNAV to 1123, increase LPV all Cats visibility ⅛ SM. Increase all MDA 60 feet and increase LNAV Cats C and D and Circling Cat D visibility ¼ SM.

MISSED APPROACH: Climb to 1100 then climbing left turn to 2300 direct WIMLU and hold.

ASOS 121.575	TOLEDO APP CON 126.1 307.0	CLNC DEL 125.6	UNICOM 123.05 (CTAF) 1
------------------------	--------------------------------------	--------------------------	----------------------------------



ELEV 623	D	TDZE 621
----------	----------	----------



REIL Rwys 4, 14 and 22 **L**
MIRL Rwys 4-22 and 14-32 **L**

