

NOTE: Chart not to scale.

ATIS 127.425
GND CON
119.975
WILLOW RUN
125.275 256.

TAKEOFF MINIMUMS

Rwys 5, 9, 23: Standard.

Rwy 27: 300-1½ or standard with a minimum climb of 209' per NM to 1000, or alternatively, with standard takeoff minimums of 200' per NM climb gradient, takeoff must occur later than 1300' prior to departure end of runway.

NOTE: For use by non-RNAV equipped aircraft only.

NOTE: When using this departure, file the appropriate depicted departure fix and route. Aircraft over HARWL must file FL220 and below. Aircraft land Cleveland (CLE) must file MAARS transition.

Turbojet departures at/above 10000, maintain 280K until advised by ATC. If unable, advise ATC prior to departure.

SPECIAL INSTRUCTIONS:

For appropriate departure control frequency, see graphic.
Use frequency depicted within the sector where first
manaid/fix for your route is located (sectors indicated by
dashed lines; frequencies in dashed box within)

(CONTINUED ON FOLLOWING PAGE)

EC-1, 17 APR 2025 to 15 MAY 2025

RADAR required. DME required.

TOP ALTITUDE:
3000

DETROIT DEP CON
WEST
118.95 284.0

DETROIT DEP CON
EAST
1343 2840

DETROIT
113.4 DXO
Chen 81

EC-1, 17 APR 2025 to 15 MAY 2025