


LOC I-UXI 108.3	APP CRS 317°	Rwy Idg TDZE Apt Elev 9002 27 28
---------------------------	------------------------	--


ILS Z or LOC Z RWY 32
GULFPORT-BILOXI INTL (GPT')

DME or RADAR required, except DME required when control tower closed.	MALSR 	MISSED APPROACH: Climb to 500 then climbing left turn to 2000 on GPT VORTAC R-245 to MUDDA INT/GPT 12 DME and hold.
Rwy 32 helicopter visibility reduction below RVR 4000 NA. Inop table does not apply to S-ILS 32. DME from GPT VORTAC. Simultaneous reception of I-UXI and GPT DME required. For inop ALS, increase S-LOC 32 all Cats visibility to RVR 5500.		

ATIS 119.45	GULFPORT APP CON ★ 127.5 254.25	GULFPORT TOWER ★ 123.7 (CTAF) 0 339.8	GND CON 120.4 348.6	UNICOM 122.95
-----------------------	---	---	-------------------------------	-------------------------



ELEV 28	TDZE 27
---------	---------



500	2000	GPT R-245	MUDDA	VICKR GPT 7 RADAR	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 72).
GS unusable when control tower closed. Only localizer minimums authorized during this period.					Remain within 15 NM
GPT 1.8					2000
0.9 NM					5.1 NM
CATEGORY					A B C D E
S-ILS 32					277/40 250 (300-¾)
S-LOC 32					380/40 353 (400-¾)
CIRCLING					520-1 640-1 760-2 760-2¼ 760-2½
					492 (500-1) 612 (700-1) 732 (800-2) 732 (800-2¼) 732 (800-2½)

SC-4, 17 APR 2025 to 15 MAY 2025

SC-4, 17 APR 2025 to 15 MAY 2025