



LOC I-ILN 110.7	APP CRS 224°	Rwy Idg TDZE 1077 Apt Elev 1077
---------------------------	------------------------	---

ILS RWY 22R (CAT II & III)

WILMINGTON AIR PARK (ILN)

DME or RADAR required for procedure entry.			ALSIF-2 	MISSED APPROACH: Climb to 1600 then climbing right turn to 3500 on MXQ VOR/DME R-250 to KLARC INT/MXQ 10 DME/RADAR and hold, continue climb-in-hold to 3500.
 	Simultaneous approach authorized. DME from MXQ VOR/DME. DME use requires simultaneous reception of I-ILN and MXQ DME.			
D-ATIS 124.925	COLUMBUS APP CON 118.85 269.275	WILMINGTON TOWER 119.475	GND CON 121.6	CLNC DEL 128.85



1600	3500	KLARC INT		VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 71).		WIZRD MXQ 11 RADAR
		MXQ R-250		AIRBO LOM MXQ 4.8	2327	2600
		IM 1180		2400	GS 3.00° TCH 55	
1125'		3.8 NM	6.2 NM			
CATEGORY	A	B	C	D		
S-ILS 22R	CAT II RA 106/12 100 DA 1177					
S-ILS 22R	CAT III RVR 06					
CATEGORY II & III ILS - SPECIAL AIRCREW & AIRCRAFT CERTIFICATION REQUIRED						

