

APP CRS
096°

Rwy Idg
11640

TDZE
883

Apt Elev
896

RNAV (RNP) Z RWY 9

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

RNP AR APCH - GPS.

▼

For uncompensated Baro-VNAV systems, procedure NA below -17°C or above 54°C. For inop ALS, increase RNP 0.30 visibility to RVR 5500.

MALSR

MISSED APPROACH: Climb to 3000 on track 096° to BLOCK and track 136° to CALIF and hold.

D-ATIS		CINCINNATI APP CON		CINCINNATI TOWER		GND CON	CLNC DEL	CPDLC
ARR	DEP	119.7	363.15 (090°-269°)	118.975	360.85 (RWY 18L/36R)	121.7	127.175	
134.375	135.3	123.875	363.15 (270°-089°)	118.3	(RWYS 18C/36C, 09/27)			
				133.325	(RWY 18R/36L)			

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 70).

JADOP

SEMSE

KAVME

RW09

5000

4000

2400

3000

GP 3.00°

TCH 52

3.1 NM

5 NM

4.5 NM

tr 096°

BLOCK

tr 136°

CALIF

CATEGORY	A	B	C	D
RNP 0.30 DA	1233/30 350 (400- $\frac{5}{8}$)			

AUTHORIZATION REQUIRED

ELEV 896

D

TDZE 883

HIRL all Rwys

TDZ/CL all Rwys except 27

COVINGTON, KENTUCKY

Orig-B 24MAR22

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

39°03'N-84°40'W

RNAV (RNP) Z RWY 9

SE-1, 17 APR 2025 to 15 MAY 2025

SE-1, 17 APR 2025 to 15 MAY 2025