

WAAS CH 42709	APP CRS 006°	Rwy Idg 10000 TDZE 896 Apt Elev 896
W36D		

RNAV (GPS) Y RWY 36R

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)



RNP APCH - GPS.



For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Simultaneous approach authorized with Rwy 36L/C. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

ALSF-2

MISSED APPROACH:
Climb to 3000 direct BAIRE and on 083° track to MOAKS and hold.

D-ATIS ARR 134.375 DEP 135.3	CINCINNATI APP CON 119.7 363.15 (090°-269°) 123.875 363.15 (270°-089°)	CINCINNATI TOWER 118.975 360.85 (RWY 18L/36R) 118.3 (RWYS 18C/36C, 09/27) 133.325 (RWY 18R/36L)	GND CON 121.7	CLNC DEL 127.175	CPDLC
---	--	---	-------------------------	----------------------------	-------



					
3000 	BAIRE 	MOAKS fr 083° 	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 70). LAPER		NUYLI 5000 GP 3.00° TCH 55
					
1.2		3.3 NM	5 NM	3.1 NM	
CATEGORY	A	B	C	D	
LPV DA	1096/18 200 (200-½)				
LNAV/VNAV DA	1340/45 444 (500-¾)				
LNAV MDA	1360/24	464 (500-½)	1360/50	464 (500-1)	
CIRCLING	1460-1	564 (600-1)	1560-1¾ 664 (700-1¾)	1560-2 664 (700-2)	