RNAV (GPS) Y RWY 12R

NORMAN Y MINETA SAN JOSE INTL (SJC)

WAAS	APP CRS		12R	12L
CH 90106	126°	Rwy Idg	8587	8831
W12A		TDZE	46	44
		Apt Elev	62	62

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1°C (31°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inoperative MALSR, increase LNAV/VNAV all Cats visibility to 1 mile and LNAV Cats C/D visibility to 1⅜ mile.

MALSR Rwy 12R

MISSED APPROACH: Climb to 4600 direct HIVAK and on track 124° to GILRO and hold.

D-ATIS	NORCAL APP CON	SAN JOSE TOWER ★	GND CON	CLNC DEL	CPDLC	UNICOM
126.95	120.1 290.25	124.0 (CTAF) L 257.6	121.7	118.0		122.95

RADAR REQUIRED

MSA RW12R 25 NM 5700

(IF) ARTAQ 1800 126° (2)

(FAF) SUNNE 126° 252

RW12R

HIVAK

MISSED APCH FIX 5 NM 305° 125° GILRO

ELEV 62 D TDZE 12R 46 TDZE 12L 44

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 75).

4600 HIVAK tr 124° GILRO

*LNAV only

ARTAQ 1800 126° SUNNE 1800 1800

*1.3 NM to RW12R

GP 3.00° TCH 58

2 NM 4.1 NM 1.3 NM

CATEGORY	A	B	C	D
LPV DA	246-½ 200 (200-½)			
LNAV/VNAV DA	371-⅝ 325 (400-⅝)	371-1 325 (400-1)		
LNAV MDA	520-½ 474 (500-½)		520-1 474 (500-1)	
SIDESTEP 12L	520-1 476 (500-1)		520-1½ 476 (500-1½)	520-2 476 (500-2)

REIL Rwy 12L
HIRL Rwys 12L-30R and 12R-30L L

SW-2, 17 APR 2025 to 15 MAY 2025