

WAAS CH 50310 W01A	APP CRS 007°	Rwy Idg TDZE 685 Apt Elev 690
--	------------------------	---

RNAV (GPS) RWY 1

ALPENA COUNTY RGNL (APN)

RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Baro-VNAV and VDP NA when using PZQ altimeter setting. For inop ALS, increase LPV all Cats visibility to ½ SM, LNAV/VNAV all Cats visibility to 1 SM and LNAV Cats C/D visibility to 1 ½ SM. When local altimeter setting not received, use PZQ altimeter setting and increase LPV DA to 1029 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 1084 feet; increase all MDA 60 feet. For inop ALS when using PZQ altimeter setting, increase LPV all Cats visibility to 1 SM.

MALSR

MISSED APPROACH:
Climb to 3500 direct HIMVO and on track 307° to RABBO and hold.

ATIS 120.675 327.05	ALPENA APP CON ★ 128.425 379.3	ALPENA TOWER ★ 121.35 (CTAF) 0 318.1	GND CON 121.9 275.8	UNICOM 122.95
-------------------------------	--	--	-------------------------------	-------------------------

ELEV 690

TDZE 685

HIRL Rwy 1-19

MIRL Rwy 7-25

REIL Rws 7, 19 and 25

TWR 768

5028 X 100

007°

	4 NM Holding Pattern	JEGOB	ONSOE	3500	HIMVO	tr 307°	RABBO
	6000 2800	187° 007°	007°	2800	1.3 NM to RW01		
	GP 3.00° TCH 52						
CATEGORY	A	B	C	D			
LPV DA		974-½	289 (300-½)				
LNAV/VNAV DA		1029-⅝	344 (400-⅝)				
LNAV MDA	1160-½	475 (500-½)	1160-1	475 (500-1)			
CIRCLING	1160-1	470 (500-1)	1220-1½ 530 (600-1½)	1300-2 610 (700-2)			

ALPENA, MICHIGAN
Orig-E 26DEC24

45°05'N-83°34'W

ALPENA COUNTY RGNL (APN)

RNAV (GPS) RWY 1

EC-1, 17 APR 2025 to 15 MAY 2025

EC-1, 17 APR 2025 to 15 MAY 2025