

LOC/DME I-HZL

110.5

Chan **42**

APP CRS

284°

Rwy Idg

4898

TDZE

1603

Apt Elev

1603

LOC RWY 28

HAZLETON RGNL (HZL)

RNAV 1-GPS required for procedure entry.
RNAV 1-GPS required from MAP to ECEDI.

▼

NA

Rwy 28 helicopter visibility reduction below ¾ SM NA. Inop table does not apply to Cats A/B. For inop ALS, increase Cat C/D visibility to 1 ⅞ SM.

MALS

MISSED APPROACH:

Climb to 4400 direct ECEDI and hold.

AWOS-3 119.975	WILKES-BARRE APP CON 126.3 256.7	CLNC DEL 121.7	UNICOM 123.0 (CTAF) 0
--------------------------	--	--------------------------	---------------------------------

ELEV **1603** **D** TDZE **1603**

4400

ECEDI

WAGDU INT I-HZL **5.9**

WEISS INT I-HZL **12.8**

One Minute Holding Pattern

6000
4200

REIL Rwy 10 **0**

MIRL Rwy 10-28 **0**

FAF to MAP 4.9 NM

Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:38

CATEGORY	A	B	C	D
S-LOC 28	2280-1	677 (700-1)	2280-1 ¾	677 (700-1 ¾)
C CIRCLING	2280-1 677 (700-1)	2400-1 797 (800-1)	2480-2 ½ 877 (900-2 ½)	2520-3 917 (1000-3)

HAZLETON, PENNSYLVANIA

Amtd 9 25APR19

40°59'N-76°00'W

HAZLETON RGNL (HZL)

LOC RWY 28