

LOC I-OSH

110.5

APP CRS

004°

Rwy Idg

8002

TDZE

808

Apt Elev

808

ILS or LOC RWY 36

WITTMAN RGNL (OSH)

⚠

When local altimeter setting not received, use Fond Du Lac altimeter setting and increase DA 31 feet and all MDA 40 feet; increase S-LOC 36 Cat C/D and Circling Cat C/D visibilities ¼ mile. For inop MALSRL when using Fond Du Lac altimeter setting, increase S-LOC 36 Cat C/D visibility to 1½ mile. Circling to Rwy 5, 23, and 31 NA at night.
* RVR 1800 authorized with the use of FD or AP or HUD to DA, NA when using Fond Du Lac altimeter setting.

MALSRL

MISSED APPROACH: Climb to 1300 then climbing right turn to 3000 on OSH R-111 to LEWKO INT/OSH 15 DME and hold.

ATIS	MILWAUKEE APP CON	OSHKOSH TOWER ★	GND CON	UNICOM
125.9	127.0 263.075	118.5 (CTAF) 290.9	132.3	122.95

ELEV 808

D

TDZE 808

REIL Rwy 18 and 27

HIRL Rwy 9-27 and 18-36

FAF to MAP 5.4 NM

Knots	60	90	120	150	180
Min:Sec	5:24	3:36	2:42	2:10	1:48

1300

3000

LEWKO

OS LOM OSH 7

Remain within 10 NM

2610

184°

004°

2700

GS 3.00° TCH 53

5.4 NM

CATEGORY	A	B	C	D
S-ILS 36 *	1008/24 200 (200-½)			
S-LOC 36	1340/24 532 (600-½)		1340/55 532 (600-1)	
CIRCLING	1340-1 532 (600-1)		1360-1½ 552 (600-1½) 1440-2 632 (700-2)	

OSHKOSH, WISCONSIN

Amdt 7C 29MAR18

43°59'N-88°33'W

WITTMAN RGNL (OSH)

ILS or LOC RWY 36

EC-3, 17 APR 2025 to 15 MAY 2025

EC-3, 17 APR 2025 to 15 MAY 2025