


WAAS CH 93534 W27A	APP CRS 274°	Rwy Idg 5648 TDZE 786 Apt Elev 808
--	------------------------	---

RNAV (GPS) RWY 27
WITTMAN RGNL (OSH)


▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Fnd D Lac altimeter setting and increase all DA 31 feet and all MDA 40 feet; increase LPV and LNAV/VNAV all Cats visibility and LNAV Cats C and D visibility ½ mile, increase Circling Cat D ¼ mile. Baro-VNAV and VDP NA with Fnd D Lac altimeter setting. Circling to Rwy's 5, 23, and 31 NA at night. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climb to 3000 direct
HETUP and hold.

ATIS 125.9	MILWAUKEE APP CON 127.0 263.075	OSHKOSH TOWER ★ 118.5 (CTAF) 0 290.9	GND CON 132.3	UNICOM 122.95
----------------------	---	--	-------------------------	-------------------------



ELEV 808	D	TDZE 786
----------	----------	----------



OSHKOSH, WISCONSIN

Amdt 1A 02APR15

43°59'N-88°33'W

WITTMAN RGNL (OSH)

RNAV (GPS) RWY 27