

VORTAC OSH
116.75
Chan 114 (Y)

APP CRS
360°

Rwy Idg
8002
TDZE
808
Apt Elev
808

VOR RWY 36
WITTMAN RGNL (OSH)

⚠

⚠

Circling to Rwy 5, 23, and 31 NA at night. When local altimeter setting not received, use Fond Du Lac altimeter setting and increase all MDA 40 feet; increase S-36 Cats C/D visibility and, Circling Cat C visibility ½ mile, increase Circling Cat D visibility ¼ mile, LAUDE fix minimums increase S-36 Cats C/D visibility to RVR 5500 and Circling Cat D visibility to 2¼ mile. For inop MALSRL, when using Fond Du Lac altimeter setting, increase LAUDE fix minimums S-36 Cats C/D visibility to 1½ mile. VDP NA with Fond Du Lac altimeter setting.

MALSRL

MISSED APPROACH:
Climbing right turn to 3000 on OSH VORTAC R-111 to LEWKO INT/ OSH 15.1 DME and hold.

ATIS 125.9	MILWAUKEE APP CON 127.0 263.075	OSHKOSH TOWER ★ 118.5 (CTAF) 290.9	GND CON 132.3	UNICOM 122.95
---------------	------------------------------------	---------------------------------------	------------------	------------------

ELEV 808 D TDZE 808

	3000	LEWKO	OSHKOSH VORTAC	
		△	6000	Remain within 10 NM
	OSHKOSH R-111			
	*1500 when using Fond Du Lac altimeter setting.			
		OSHKOSH 2.9	LAUDE OSH 3.5	
		2.97° TCH 52		
		1.3 NM	0.6 NM	
CATEGORY	A	B	C	D
S-36	1460/24	652 (700-½)	1460-1¾	652 (700-1¾)
CIRCLING	1460-1	652 (700-1)	1460-17½	1460-2
			652 (700-1¾)	652 (700-2)
	LAUDE FIX MINIMUMS			
S-36	1280/24	472 (500-½)	1280/50	472 (500-1)
CIRCLING	1280-1	1300-1	1360-1½	1440-2
	472 (500-1)	492 (500-1)	552 (600-1½)	632 (700-2)

OSHKOSH, WISCONSIN
Amdt 17A 02APR15

43°59'N-88°33'W

WITTMAN RGNL (OSH)
VOR RWY 36