

WAAS CH 86410 W30A	APP CRS 304°	Rwy Idg TDZE Apt Elev	6000 549 549
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 30

JEFFERSON CITY MEML (JEF)


RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Circling Rwy 9 NA at night. When local altimeter setting not received, use COU altimeter setting and increase LPV DA to 879 feet; increase LNAV/VNAV DA to 1402 feet and all visibilities ¼ SM. Increase all MDAs 80 feet and LNAV visibility Cats B/C/D ¼ SM, and Circling visibility Cats A/B/C ¼ SM. Baro-VNAV and VDP NA when using COU altimeter setting. For inop ALS increase LNAV/VNAV visibility all Cats to 2½ SM. For inop ALS when using COU altimeter setting, increase LPV visibility all Cats to 1 SM and increase LNAV visibility Cats C/D to 2½ SM.


MALSR

MISSED APPROACH: Climb to 3000 direct GIBSN and hold.

ASOS 133.625	MIZZU APP CON 124.375 353.925	JEFFERSON CITY TOWER ★ 125.6 (CTAF) 0	GND CON 121.7	UNICOM 122.95
------------------------	---	--	-------------------------	-------------------------



ELEV 549	TDZE 549
-----------------	-----------------



REIL Rwy 9, 12, and 27 **0**
MIRL Rwy 9-27
HIRL Rwy 12-30 **0**

3000	GIBSN	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 50).			
		ERINE	FATPI	4 NM Holding Pattern	
		2 NM to RW30			
		2 NM	2.3 NM	6.1 NM	
CATEGORY	A	B	C	D	
LPV DA	799-½ 250 (300-½)				
LNAV/VNAV DA	1322-1¾ 773 (800-1¾)				
LNAV MDA	1240-½ 691 (700-½)		1240-1½ 691 (700-1½)		
CIRCLING	1280-1 731 (800-1)		1320-2¼ 771 (800-2¼)		1560-3 1011 (1100-3)