


WAAS CH 45913 W14A	APP CRS 141°	Rwy Idg TDZE 258 Apt Elev 258
--	------------------------	---


RNAV (GPS) RWY 14
SHREVEPORT RGNL (SHV)

RNP APCH. ⚠ ASR	For inop ALS, increase LNAV Cat C and D visibility to RVR 6000. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -6°C or above 54°C.	ALSF-2 ⓐ	MISSED APPROACH: Climb to 3000 direct COBAV and hold, continue to climb-in-hold to 3000.
-----------------------	--	-------------	--

ATIS 128.45	SHREVEPORT APP CON 119.9 335.55	SHREVEPORT TOWER 121.4 236.775	GND CON 121.175 236.775	CLNC DEL 124.65
-----------------------	---	--	-----------------------------------	---------------------------



ELEV 258	D	TDZE 258
----------	----------	----------



REIL Rws 6 and 24
TDZ/CL Rwy 14
HIRL Rwy 14-32
MIRL Rwy 6-24

4 NM

Holding Pattern

BABYE

3000

↑

COBAV

✦

6000

← 316°

2500

→ 136°

GP 3.00°

TCH 51

141°

JAVEE

1500

*1.1 NM to RWY14

*LNAV only.

1500

6.3 NM

2.6 NM

1.1 NM

RWY14

CATEGORY	A	B	C	D
LPV DA		458/18	200 (200-½)	
LNAV/VNAV DA		640/40	382 (400-¾)	
LNAV MDA	660/24	402 (500-½)	660/40	402 (500-¾)
C CIRCLING	760-1	502 (600-1)	980-2 722 (800-2)	1100-2¾ 842 (900-2¾)