

WAAS CH 90509 W14A	APP CRS 144°	Rwy Idg 13503 TDZE 1169 Apt Elev 1189
--	------------------------	--



RNAV (GPS) Y RWY 14L
GRANT COUNTY INTL (MWH)

RNP APCH.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 36°C.
▲ Baro-VNAV and VDP NA when using Ephraht altimeter setting. When local altimeter setting not received, use Ephraht altimeter setting: increase all DA 36 feet and all MDA 40 feet, increase LNAV/VNAV visibility all Cats ½ SM, LNAV Cats C and D and Circling Cat D ¼ SM.

MISSED APPROACH: Climb to 4000 direct HEDBI and on track 124° to UPBOB and hold.

ATIS 119.05	GRANT COUNTY APP CON ★ 126.4 379.95	GRANT COUNTY TOWER ★ 118.25 (CTAF) 0 257.8 (EAST) 128.0 257.8 (WEST)	GND CON 121.9	UNICOM 122.95
----------------	--	--	------------------	------------------



4 NM Holding Pattern

VGS and RNAV glidepath not coincident (VGS Angle 3.00/TCH 75).

JUKRI

ILARE

4000

324°

144°

3000

144°

3000

6.4 NM

3.8 NM

0.7

1.1 NM

RW14L

VIMFY 1.8 NM to RW14L

*1.1 NM to RW14L

*1780

GP 3.00° TCH 52

CATEGORY	A	B	C	D
LPV DA	1369- ³ / ₄	200 (200- ³ / ₄)		
RNAV/VNAV DA	1436- ⁷ / ₈	267 (300- ⁷ / ₈)		
RNAV MDA	1580-1	411 (400-1)	1580-1 ¹ / ₂	411 (400-1 ¹ / ₂)
CIRCLING	1660-1	471 (500-1)	1680-1 ¹ / ₂ 491 (500-1 ¹ / ₂)	1820-2 631 (700-2)

RNAV (GPS) Y RWY 14L