

RNAV 1 - DME/DME/IRU or GPS.

RADAR required.

ATIS
125.025
CLNC DEL
118.25
GND CON
121.9
PONTIAC TOWER ★
120.5 (CTAF)
DETROIT DEP CON
132.35 284.0

WSA PTK 25 NM

2900

↔ 275° ↔

095°

↑

N

TAKEOFF MINIMUMS:

Rwys 18, 36: NA - Environmental.

Rwys 9L/R, 27L/R: Standard.

NOTE: Chart not to scale.

TOP ALTITUDE:
ASSIGNED BY ATC

HUBBY
*5000
*3200
(34)

SILAP
*5000
*2300
*3000
(24)

GETCH
5000
*2400
274°
(70)

MONEE
5000
323°
(20)

MIGGY
5000
323°
(18)

JAXII

NOTE: Jet departures at/above 10000,
maintain 280K until advised by ATC.

NOTE: GETCH TRANSITION: For use by KMKE area
arrivals only, or as assigned by ATC.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 9L/R: Climb on heading 095° or as assigned by ATC,
thence....

TAKEOFF RUNWAYS 27L/R: Climb on heading 275° or as assigned by ATC,
thence....

....for RADAR vectors to JAXII, then on track 323° to MIGGY, then on
(transition). Maintain 17000 or as assigned by ATC, expect filed altitude
10 minutes after departure.

GETCH TRANSITION (MIGGY3.GETCH):

HUBBY TRANSITION (MIGGY3.HUBBY):

SILAP TRANSITION (MIGGY3.SILAP):

MIGGY THREE DEPARTURE (RNAV)

(MIGGY3.MIGGY) 16MAY24

PONTIAC, MICHIGAN

OAKLAND COUNTY INTL (PTK)

EC-1, 17 APR 2025 to 15 MAY 2025

EC-1, 17 APR 2025 to 15 MAY 2025