

WAAS CH 60909 W29A	APP CRS 291°	Rwy Idg 6525 TDZE 871 Apt Elev 871
--	------------------------	---

RNAV (GPS) RWY 29
CENTRAL IL RGNL/BLOOMINGTON-NORMAL (BMI)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using General Downring-Peoria Intl altimeter setting. When local altimeter setting not received, use General Downring-Peoria Intl altimeter setting: increase all DA 116 feet and all MDA 120 feet; increase LPV all Cats visibility to RVR 3500; LNAV/VNAV all Cats and LNAV Cats C/D visibility ¾ mile, and Circling Cats C/D visibility ¼ mile. For inoperative MALSRs when using General Downring-Peoria Intl Regional altimeter setting increase LPV all Cats visibility ½ mile, and LNAV Cat C/D visibility ¾ mile.

MALS

                                       

MISSED APPROACH:
Climb to 2500 direct
ZEXED and hold.

ATIS	SAINT LOUIS APP CON
119.575	128.725 256.9

BLOOMINGTON TOWER ★
124.6 (CTAF) **L** 269.575

GND CON
121.65

UNICOM
122.95

Procedure NA for arrivals at JILLY
via V173 northeast bound and
V227 northwest bound.

ELEV 871		TDZE 871
----------	---	----------

[illegible]

TDZ/CL Rwy 20 **L**
HIRL Rwys 2-20 and 11-29 **L**

[illegible]

CATEGORY		A	B	C	D
LPV	DA	1121/24 250 (300-½)			
INAV/ VNAV	DA	1304/50 433 (500-1)			
INAV	MDA	1460/24 589 (600-½)	1460-1¼ 589 (600-1¼)		
C CIRCLING		1460-1 589 (600-1)	1620-2¼ 749 (800-2¼)	1620-2½ 749 (800-2½)	

BLOOMINGTON/NORMAL, ILLINOIS
Amdt 1A 15OCT15

CENTRAL IL RGNL/BLOOMINGTON-NORMAL (BMI)

40°29'N-88°55'W

RNAV (GPS) RWY 29