

WAAS CH 58016 W31A	APP CRS 308°	Rwy Idg TDZE 1885 Apt Elev 1915
--	------------------------	---

RNAV (GPS) RWY 31

POCONO MOUNTAINS RGNL (MPO)

⚠

Baro-VNAV NA when using Wilkes-Barre/Scranton altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F).
Rwy 31 helicopter visibility reduction below ¾ SM NA. DME/DME RNP-0.3 NA.
When local altimeter setting not received, use Wilkes-Barre/Scranton altimeter setting: increase LPV DA to 2403 feet and visibility ¼ SM, LNAV/VNAV DA to 2446 feet and visibility ⅓ SM; increase all MDAs 180 feet and visibility LNAV Cat C/D ⅓ SM and Circling Cat C/D ½ SM. Circling Rwy 23 NA at night.

MISSED APPROACH:

Climb to 4200 direct RYANF and on track 228° to WHITT and hold.

ASOS 120.275	WILKES-BARRE APP CON 126.3 256.7	CLNC DEL 125.3	UNICOM 122.7 (CTAF) 0
------------------------	--	--------------------------	---------------------------------

RYANF
A 2309
A 2278
A 2206 ±
A 2059 ±
RW31
(FAF) YUKPU
3400
308°
(7.8)
(IF) WONNU
(IAF) SCOUPE
4000
275° (3.8)
A 2504
WHITT
A 047
227°
5 NM
Procedure NA for arrivals at BEERS on T221, V149 northbound and on V232 northwest bound.
BEERS
4200
106°
(10.2)
4000
038°
(11.7)
(IAF) ZUCRY
MSA RW31 25 NM
4000

ELEV 1915

TDZE 1885

4200

RYANF

tr 228°

WHITT

VGSI and RNAV glidepath not coincident (VGSI Angle 3.50/TCH 40).

WONNU

YUKPU

3400

308°

4000

GP 3.00°
TCH 55

308°

4.6 NM

7.8 NM

CATEGORY	A	B	C	D
LPV DA	2224-1½ 339 (400-1½)			
LNAV/VNAV DA	2267-1¼ 382 (400-1¼)			
LNAV MDA	2320-1	435 (500-1)	2320-1½	435 (500-1½)
CIRCLING	2420-1 505 (600-1)	2500-1 585 (600-1)	2600-2 685 (700-2)	2660-2½ 745 (800-2½)

MOUNT POCONO, PENNSYLVANIA
Amdt 2D 24MAY18

POCONO MOUNTAINS RGNL (MPO)
RNAV (GPS) RWY 31

41°08'N-75°23'W