

WAAS CH 69623 W27A	APP CRS 270°	Rwy Idg TDZE 239 Apt Elev 246
--	------------------------	---

RNAV (GPS) RWY 27

WINDHAM (IJD)


▼

▲

Procedure NA at night. DME/DME RNP-0.3 NA. Rwy 27 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Windsor Locks altimeter setting and increase all MDA 80 feet, increase LP and LNAV Cat B and Circling Cats A/B visibility ¼ SM, increase LP, LNAV and Circling Cat C visibility ½ SM.

MISSED APPROACH:
Climbing left turn to
2600 direct ORW
VOR/DME and hold.

ASOS 133.675	BRADLEY APP CON 127.8 269.325	CLNC DEL 128.6	UNICOM 122.975 (CTAF) 0
------------------------	---	--------------------------	-----------------------------------



ELEV 246	TDZE 239	Visual Segment - Obstacles.			
		2600	ORW	HHOTT	
		HUVUX 3.1 NM to RW27		4 NM Holding Pattern	
		RW27	LINKS	2200	
		1260		2500	
		3.1 NM 2.9 NM 6 NM			
		CATEGORY	A	B	C D
		LP MDA	940-1 701 (700-1)	940-2 701 (700-2)	NA
		LNAV MDA	960-1 721 (800-1)	960-2 721 (800-2)	NA
		CIRCLING	980-1 734 (800-1)	1120-2½ 874 (900-2½)	NA