

WAAS
CH **82438**
W30A

APP CRS
305°

Rwy Idg **4000**
TDZE **1121**
Apt Elev **1125**


RNAV (GPS) RWY 30
NORTHEAST IOWA RGNL (CCY)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Waterloo altimeter setting and increase all DA 110 feet and visibility ¼ mile. Increase all MDA 120 feet, increase LNAV Cat C visibility ¾ mile, and Circling visibility Cat C ½ mile. VDP and Baro-VNAV NA when using Waterloo altimeter setting. Circling Rwy 4-22 and 18-36 NA.

MISSED APPROACH: Climb to 4000 direct JUKAG and hold, continue climb-in-hold to 4000.

AWOS-3 125.525	WATERLOO APP CON ★ 118.9 251.15	UNICOM 122.8 (CTAF) ①
--------------------------	---	---------------------------------



ELEV **1125**

TDZE **1121**

4000

JUKAG

VGS and RNAV glidepath not coincident (VGS Angle 3.00/TCH 27).

* LNAV only

ZUMAM 2 NM to RW30

NUPZI 2700

IJIBU 4000

4 NM Holding Pattern

1 NM

1 NM

2.9 NM

6.1 NM

GP 3.00°

TCH 40

CATEGORY	A	B	C	D
LPV DA	1371-1	250 (300-1)		NA
LNAV/VNAV DA	1371-1	250 (300-1)		NA
LNAV MDA	1460-1	339 (400-1)		NA
CIRCLING	1520-1 395 (400-1)	1580-1 455 (500-1)	1760-1¾ 635 (700-1¾)	NA