

WAAS CH 72707 W02A	APP CRS 023°	Rwy Idg 5197 TDZE 826 Apt Elev 827
--	------------------------	---

RNAV (GPS) RWY 2


JOHN F KENNEDY MEML (ASX)

RNP APCH.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -28°C or above 54°C.
▲ Rwy 2 helicopter visibility reduction below $\frac{3}{4}$ SM NA. Baro-VNAV and VDP NA when using Ironwood altimeter setting. When local altimeter setting not received, use Ironwood altimeter setting and increase all DA 132 feet and all MDAs 140 feet; increase LPV all Cats and LNAV Cat C/D visibility $\frac{3}{4}$ SM, LNAV/VNAV all Cats and Circling Cat C/D visibility $\frac{1}{2}$ SM.

MISSED APPROACH:
Climb to 3200 direct
HOSUT and hold.

ASOS 126.775	MINNEAPOLIS CENTER 126.45 276.4	GCO 122.25	UNICOM 122.8 (CTAF) 0
------------------------	---	----------------------	--



4 NM Holding Pattern

FOMLO

EICU

HEPED 2.7 NM to RW02

RW02

6000

3600

203°

023°

3000

1720

5.9 NM


4 NM

1.3

1.4

3200 HOSUT

*INAV only



RNAV (GPS) RWY 2