

WAAS CH 61114 W08B	APP CRS 079°	Rwy Idg 7414 TDZE 462 Apt Elev 463
--	------------------------	---

RNAV (GPS) RWY 8R
SPIRIT OF ST LOUIS (SUS)

RNP APCH - GPS.

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Baro-VNAV and VDP NA when using St Louis Lambert Intl altimeter setting. When local altimeter setting not received, use St Louis Lambert Intl altimeter setting and increase all DA 57 feet all MDA 60 feet, increase visibility LNAV/VNAV all Cats and LNAV Cats C/D ½ mile, and Circling Cat C ¼ mile. For inop MALSR, increase LNAV/VNAV all Cats DA visibility to 2½ mile and LNAV Cats C/D visibility to 1¾ mile. For inop MALSR when using St Louis Lambert Intl altimeter setting, increase LNAV Cats C/D visibility to 1¾ mile.

#RVR 1800 authorized with use of FD or AP or HUD to DA, NA when using St Louis Lambert Intl altimeter setting.

MALSR




MISSED APPROACH:
Climb to 3000 direct
HUGGE and right turn
on track 175° to
BNANA and right turn
on track 272° to
DERDE and hold.


ATIS 134.8	ST. LOUIS APP CON 126.5 254.3	SPIRIT TOWER★ 124.75 (CTAF) 0 257.2	GND CON 121.7	CLNC DEL 133.1	ST. LOUIS CLNC DEL 121.7 (when tower closed)	UNICOM 122.95
----------------------	---	---	-------------------------	--------------------------	---	-------------------------

1128A


Procedure NA for arrival at FTZ VORTAC
on airway radials 082 CW 150.

1648 Δ

ELEV 463	D	TDZE 462
----------	----------	----------



CATEGORY	A	B	C	D
LPV DA#	662/24 200 (200-½)			
LNAV/VNAV DA	1129-1⅞ 667 (700-1⅞)			
LNAV MDA	1040/24	578 (600-½)	1040-1¼	578 (600-1¼)
CIRCLING	1100-1 637 (700-1)	1140-1 677 (700-1)	1160-2 697 (700-2)	1360-3 897 (900-3)



MIRL Rwy 8L-26R **L**
HIRL Rwy 8R-26L **L**