


WAAS CH 40237 W14A	APP CRS 141°	Rwy Idg TDZE Apt Elev	3851 1117 1122
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 14
WEBSTER CITY MUNI (EBS)


⚠ Baro-VNAV NA when using Clarion altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Clarion altimeter setting and increase all DAs 49 feet, and all MDA 60 feet; increase LNAV/VNAV all Cats visibility 1/8 mile. Helicopter visibility reduction below 3/4 SM NA.

MISSED APPROACH: Climb to 3000 direct OLT OE and hold.

AWOS-3 127.825	MINNEAPOLIS CENTER 134.0 288.3	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



ELEV 1122	TDZE 1117
-----------	-----------



VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 32).				3000	OLT OE
4 NM Holding Pattern HOGOD				↑	✦
3000 ← 321°				*LNAV only	
GP 3.00° TCH 40				ZOKOV 1.6 NM to RW14	
2700				RW14	
7.4 NM				*1640	
3.3 NM					
1.6 NM					
CATEGORY	A	B	C	D	
LPV DA	1367-1	250 (300-1)	NA		
LNAV/VNAV DA	1463-1 1/4	346 (400-1 1/4)	NA		
LNAV MDA	1540-1	423 (500-1)	NA		
CIRCLING	1600-1	478 (500-1)	NA		

NC-3, 17 APR 2025 to 15 MAY 2025

NC-3, 17 APR 2025 to 15 MAY 2025