

WAAS CH 69423 W28A	APP CRS 284°	Rwy Idg TDZE 1189 Apt Elev 1191	5504
--	------------------------	---	-------------

RNAV (GPS) RWY 28

KNOX COUNTY (4I3)

RNP APCH.
▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 36°C.

MISSED APPROACH: Climb to 3000 direct BONIF and hold.

AWOS-3 126.05	COLUMBUS APP CON 125.95 317.775	CLNC DEL 119.45	UNICOM 123.05 (CTAF) 0
-------------------------	---	---------------------------	----------------------------------

MISSED APCH FIX

BONIF

4 NM

MSA RW 28 25 NM

3100

2800

1640 Δ Δ 1497 $\pm$ Δ 1330 1273 $\pm$ RW28 SLAPT 1.7 NM to RW28 (FAF) WEBUB 2700 284° (6.9) 104° 4 NM HOLD 6000 2800 284° 2800 NoPT 014° (9.8) 305° (13.6) 2800 NoPT 305° (13.6)

Procedure NA for arrival on APE VORTAC airway radials 055 CW 168.

APPLETON APE 3000 099° (13.5)

(IAF) TUCUG (IAF) ROSCO

ELEV 1191	TDZE 1189
-----------	-----------

10 28 284°

5504 x 100

3000 BONIF

*LNAV only

SLAPT 1.7 NM to RW28 *1 NM to RW28 WEBUB 2700 PATIE 104° 284° 6000 2800 GP 3.00° TCH 40°

CATEGORY	A	B	C	D
LPV DA		1389-1	200 (200-1)	
LNAV/VNAV DA		1439-1	250 (300-1)	
LNAV MDA		1540-1	351 (400-1)	