

|                                        |                        |                             |                                         |
|----------------------------------------|------------------------|-----------------------------|-----------------------------------------|
| WAAS<br>CH <b>53328</b><br><b>W01A</b> | APP CRS<br><b>006°</b> | Rwy Idg<br>TDZE<br>Apt Elev | <b>6503</b><br><b>346</b><br><b>346</b> |
|----------------------------------------|------------------------|-----------------------------|-----------------------------------------|

RNAV (GPS) RWY 1

EVERETT-STEWART RGNL (UCY)

▼

▲ NA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. VDP and Baro-VNAV NA when using Dyersburg altimeter setting. When local altimeter setting not received, use Dyersburg altimeter setting and increase all DA 72 feet and all MDA 80 feet, increase LNAV/VNAV all Cats visibility to 1½ SM, LNAV Cat C/D visibility to 1½ SM, and Circling Cat D visibility to 2½ SM. For inoperative ALS, increase LNAV/VNAV and LNAV all Cats visibility to 1 SM. For inoperative ALS when using Dyersburg altimeter setting, increase LPV all Cats visibility to ¾ SM, LNAV/VNAV all Cats visibility to 1¼ SM, and LNAV Cat D visibility to 1¾ SM. Inoperative table does not apply to LPV all Cats and LNAV Cats C/D.

ODALS

MISSED APPROACH:  
Climb to 2900 direct  
LOYIG and hold.

|                          |                                        |                                 |
|--------------------------|----------------------------------------|---------------------------------|
| AWOS-3<br><b>135.325</b> | MEMPHIS CENTER<br><b>133.65 292.15</b> | UNICOM<br><b>122.7 (CTAF) 0</b> |
|--------------------------|----------------------------------------|---------------------------------|

