

WAAS CH 49032 W14A	APP CRS 142°	Rwy Idg TDZE Apt Elev	4899 1132 1136
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 14

MORRIS MUNI/CHARLIE SCHMIDT FLD (MOX)

RNP APCH-GPS.

▼

Baro-VNAV and VDP NA when using BBB altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use BBB altimeter setting and increase LPV and LNAV/VNAV DA to 1440 feet. Increase all MDAs 60 feet and visibility LNAV Cat C ½ SM and visibility Circling Cat C ¼ SM.

⚠

MISSED APPROACH: Climb to 3500 direct EXJUP and hold.

AWOS-3PT 118.6	MINNEAPOLIS CENTER 126.1 269.2	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------

ELEV 1136

TDZE 1132

	ZITOG		EBYEX		YOPCU		RWY 14	
	4 NM Holding Pattern		3000		1800		1 NM to RWY 14	
	6000 ← 322°		142° →		3000		1 NM to RWY 14	
	3000		142°		3000		1 NM to RWY 14	
	GP 3.00°		TCH 40		8 NM		3.8 NM	
CATEGORY	A		B		C		D	
LPV DA	1382-1		250 (300-1)				NA	
LNAV/VNAV DA	1382-1		250 (300-1)				NA	
LNAV MDA	1480-1		348 (400-1)				NA	
CIRCLING	1560-1 424 (500-1)		1600-1 464 (500-1)		1860-2 724 (800-2)		NA	

MORRIS, MINNESOTA
Amdt 2A 31OCT24

MORRIS MUNI/CHARLIE SCHMIDT FLD (MOX)

45°34'N-95°58'W

RNAV (GPS) RWY 14

NC-1, 17 APR 2025 to 15 MAY 2025

NC-1, 17 APR 2025 to 15 MAY 2025