

VOR/DME DTL	APP CRS	Rwy Idg	5201
111.2	314°	TDZE	1372
Chan 49		Apt Elev	1396

VOR RWY 32

DETROIT LAKES/WETHING FLD (DTL)

NA

Circling NA to Rwy's 18 and 36. VDP NA with Park Rapids altimeter setting. When local altimeter setting not received, use Park Rapids altimeter setting and increase all MDA 100 feet and visibility Cat A ¼ SM, Cats C and D ½ SM and Circling Cats A and C ¼ SM, Cat D ½ SM. DUWIZ fix minimums: increase visibility Cats C and D ¼ SM. For inop ALS, increase S-32 Cats C and D visibility to 2½ SM. Inop table does not apply to S-32 Cats C and D when using Park Rapids altimeter setting.

MALSF

MISSED APPROACH:

Climb to 2500 then climbing left turn to 3200 direct DTL VOR/DME and hold, continue climb-in-hold 3200.

AWOS-3PT	MINNEAPOLIS CENTER	UNICOM
119.075	126.1 269.2	122.8 (CTAF)

The chart displays the Detroit Lakes, Minnesota, area. Key features include:

- VOR RWY 32:** Frequency 111.2, Channel 49, MDA 1372, ELEV 1396.
- DTL VOR/DME:** Frequency 119.075, Channel 49, MDA 1372, ELEV 1396.
- DUWIZ DTL:** Frequency 3.3, MDA 1372, ELEV 1396.
- STAR:** Frequency 42.3, MDA 1372, ELEV 1396.
- ROLAG AXN:** Frequency 65.6, MDA 1372, ELEV 1396.
- IAF DETROIT LAKES:** Frequency 111.2, Channel 49, MDA 1372, ELEV 1396.
- MSA DTL 25 NM:** MDA 1372, ELEV 1396.
- Obstacles:** Various obstacles are shown with their MSL and AGL altitudes.
- Navigation:** The chart includes various navigational aids, including VOR, DME, and DTL, and shows the flight path for RWY 32.

The diagram shows the HIRL Rwy 14-32 and REIL Rwy 14. Key features include:

- HIRL Rwy 14-32:** Frequency 111.2, Channel 49, MDA 1372, ELEV 1396.
- REIL Rwy 14:** Frequency 111.2, Channel 49, MDA 1372, ELEV 1396.
- Navigation:** The diagram shows the flight path for RWY 32, including the VOR/DME and DTL VOR/DME.

2500	3200	DTL	DTL VOR/DME	*2300 when using Park Rapids altimeter setting.
CATEGORY	A	B	C	D
S-32	2200-¾ 828 (900-¾)	2200-1 828 (900-1)	2200-2 828 (900-2)	828 (900-2)
CIRCLING	2200-1 804 (900-1)	2200-1¼ 804 (900-1¼)	2200-2½ 804 (900-2½)	804 (900-2½)
DUWIZ FIX MINIMUMS				
S-32	1760-¾ 388 (400-¾)	1760-7/8 388 (400-7/8)	1760-7/8 388 (400-7/8)	388 (400-7/8)
CIRCLING	1820-1 424 (500-1)	1860-1 464 (500-1)	2080-2 684 (700-2)	2140-2½ 744 (800-2½)

DETROIT LAKES, MINNESOTA

Amtd 2 25FEB21

46°50'N-95°53'W

DETROIT LAKES/WETHING FLD (DTL)

VOR RWY 32