

WAAS CH 93616 W17A	APP CRS 171°	Rwy Idg TDZE 93 Apt Elev 101	5705
--	------------------------	--	-------------

RNAV (GPS) RWY 17

LOWCOUNTRY RGNL (R.B.W)


▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Charleston Intl/AFB altimeter setting. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Charleston AFB/Intl altimeter setting: increase LPV DA to 421 feet and LNAV/VNAV DA to 587 feet and all MDA 80 feet; increase LPV visibility all Cats ½ mile; increase LNAV/VNAV visibility all Cats, LNAV Cats C/D, and Circling Cat D visibility ¼ mile; increase Circling Cat C visibility ½ mile.

MISSED APPROACH:
Climb to 2100 direct LATNY and on track 081° to CIGLO and track 003° to LAMKE and hold.

AWOS-3PT 118.725	CHARLESTON APP CON 120.7 306.925	UNICOM 122.8 (CTAF) 0
----------------------------	--	---------------------------------



GP 3.00°
TCH 40

2100 LATNY tr 081° CIGLO tr 003° LAMKE

2000 171° 1700 1700 1300 3.7 NM to RW17 1.4 NM to RW17

*LNAV only.

GP 3.00° TCH 40

6.1 NM 1.2 NM 2.3 NM 1.4 NM

CATEGORY A B C D

LPV DA 343-1 250 (300-1)

LNAV/VNAV DA 508-1½ 415 (500-1½)

LNAV MDA 580-1 487 (500-1) 580-1¾ 487 (500-1¾)

CIRCLING 620-1 519 (600-1) 640-1 539 (600-1) 700-1½ 599 (600-1½) 700-2 599 (600-2)

REIL Rwy 23
MIRL Rwy 5-23 0